

#### **PRODUCT SPECIFICATION**

Winel BV PO Box 70, 9400 AB Assen, The Netherlands

> info@winel.nl www.winel.nl

# Forepeak yacht hatch (weather tight)

(article code 471.)

# **■** Forepeak yacht hatch

The Forepeak yacht hatch is a weather tight hatch which is compliant to yacht standards without compromising the functionality of the hatch. It is supplied as a completely finished and tested hatch, ready to weld in.

## Class society approval

According demarcation overview class society.

## **■** ■ Specifications

#### **Coaming**

6 mm aluminium (incl. spring support in aluminium).

6 mm stainless steel AISI316L (incl. spring support in stainless steel).

6 mm steel (incl. spring support in stainless steel).

The spring axle is standard executed in stainless steel.

#### Cover

6 mm steel (lugs in stainless steel).

6 mm aluminium (lugs in aluminium).

6 mm stainless steel AISI316L (lugs in stainless steel).

# **Closing system**

4 Stainless steel axles: which are locked in pockets, through POM wedges which are placed inside the lock pockets.







# **Operation**

The hatch is standard delivered without an operation device. Please check the option list for the various possibilities.

#### Insulation

The hatch is standard delivered without insulation. Please check the option list for the various possibilities.

## **Hinges**

The hatch is equipped with stainless steel high gloss polished spring loaded hinges.

## **Bearing material**

Orkot® Marine Bearings are manufactured from a unique synthetic composition incorporating solid lubricants for dry running to ensure outstanding wear life. Virtually no swelling in sea water and very low thermal coefficient of expansion provide dimensional stability in arctic and tropical seas. They do not corrode or promote corrosion of the housing and tolerate both edge loading and misalignment.







## **PRODUCT SPECIFICATION**

Winel BV PO Box 70, 9400 AB Assen, The Netherlands

> info@winel.nl www.winel.nl

# Forepeak yacht hatch (weather tight)

(article code 471.)

#### **Available sizes**

Clear diameter: 600, 650, 700, 750 and 800 mm. Clear height: 400, 450, 500, 550 and 600 mm.

Based on the chosen options the minimum clear opening could be different than above mentioned.

## **Surface treatment**

Shot blasted SA2, 5 and primed with one layer of AWL hull guard primer, min. 20 Mu. Standard stainless steel parts are passivated and pickled.

# Available options

See option list yacht hatches. Document: PS.YH.37. Option list Forepeak yacht hatches.

#### Packing

Packed on a wooden pallet and sealed with shrinking foil.

## **■** Available article codes

Please specify article codes when asking for quotation as follows:

471.11.COxH	Forepeak yacht hatch, aluminium coaming, steel cover, COxH
471.12.COxH	Forepeak yacht hatch, aluminium coaming, aluminium cover, COxH
471.13.COxH	Forepeak yacht hatch, aluminium coaming, stainless steel cover, COxH
471.21.COxH	Forepeak yacht hatch, stainless steel coaming, steel cover, COxH
471.22.COxH	Forepeak yacht hatch, stainless steel coaming, aluminium cover, COxH
471.23.COxH	Forepeak yacht hatch, stainless steel coaming, stainless steel cover, COxH
471.31.COxH	Forepeak yacht hatch, steel coaming, steel cover, COxH
471.32.COxH	Forepeak yacht hatch, steel coaming, aluminium cover, COxH
471.33.COxH	Forepeak yacht hatch, steel coaming, stainless steel cover, COxH

Specify clear opening :  $CO \times H = clear$  opening, diameter  $\times L$  height

Specify options : article code

Specify Class Society Quantity