



A30 & B30 Marine doors

Shipdoor A-30 "A30 Poki-L / LMD-A30-Poki-L"

A-30 single-leaf hinged fire-door, type "A30 Poki-L / LMD-A30-Poki-L",
GL-EC-Certificate 47727-03 Lux, ABS, RRS, TC, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.
Doorleaf composite plate insulated with mineral wool, both sides with galvanised steel sheet.
Frame like a z-profile around the door or with sill like a l-, u- or flatbar.
Frame for welding and bolting.
Doorleaf and frame primed.

Maximum size: 960 x 1990 mm

Weight: 30 kg/m² / doorleaf

Options:

- doorleaf with doorcloser
- doorleaf pvc-coated steel sheet
- doorleaf and frame stainless steel sheet
- doorleaf with round corners
- frame with sealing
- doorleaf with recessed handles
- doorleaf with concealed doorcloser
- doorleaf with concealed hinges
- doorleaf 40mm thick
- clamping frame



Shipdoor A-30 "LMD-H1-W"

A-30 single-leaf hinged fire-door, type "LMD-H1-W",
GL-EC-Certificate 26557-05 Lux, ABS, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.
Doorleaf both sides with 1,0 mm galvanised steel sheet.
Frame like a z-profile around the door or with sill like a l-, u- or flatbar.
Frame for welding and bolting.
Doorleaf and frame primed.

Maximum size: 1200 x 2050 mm
Weight: 50 kg/m² / doorleaf

Options:

- doorleaf with doorcloser
- doorleaf pvc-coated steel sheet
- doorleaf and frame stainless steel sheet
- frame with sealing
- doorleaf with A/30-window
- doorleaf with panic bar
- doorleaf with lever dogs
- doorleaf with recessed handles
- doorleaf with electromagnet



Shipdoor B-30 "B30 CODO / LMD-CODO"

B-30 single-leaf hinged fire-door, type "B30 CODO / LMD CODO",
GL-EC-Certificate 47728-03 Lux, ABS, RRS, TC, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.
Doorleaf composite plate insulated with mineral wool, both sides with galvanised steel sheet.
Frame like a z-profile around the door or with sill like a l-, u- or flatbar.
Frame for welding and bolting.
Doorleaf and frame primed.

Maximum size: 960 x 1990 mm
Weight: 30 kg/m² / doorleaf

Options:

- doorleaf with doorcloser
- doorleaf pvc-coated steel sheet
- doorleaf and frame stainless steel sheet
- doorleaf with round corners
- frame with sealing
- doorleaf with recessed handles
- doorleaf with concealed doorcloser
- doorleaf with concealed hinges
- doorleaf 40mm thick
- clamping frame

