



A60 Marine doors

Shipdoor A-60 "A60 Poki / LMD-H1 / LMD-H1-G"

A-60 single-leaf hinged fire-door, type "A60 Poki / LMD-H1 / LMD-H1-G",
GL-EC-Certificate 42842-02 Lux, ABS, RRS, TC, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.

Doorleaf both sides with 1,0 mm galvanized steel sheet.

Frame like a z-profile around the door or with sill like a l-, u- or flatbar.

Frame for welding and bolting

Doorleaf and frame primed.

Maximum size: 1200 x 2050 mm

Options:

doorleaf with doorcloser

hoseport

doorleaf with A/60-window

doorleaf pvc-coated steel plates

doorleaf and frame stainless steel sheet

frame with sealing

doorleaf with concealed doorcloser

clamping frame

doorleaf with panic bar

doorleaf with lever dogs

doorleaf with recessed handles

doorleaf with electromagnet



Shipdoor A-60 "LMD-H1-L"

A-60 single-leaf hinged fire-door, type "LMD-H1-L",
GL-EC-Certificate 32849-06 Lux, ABS, RRS, TC, USCG.

Door complete with lock as per DIN 18250 and handle, lift lock and contact.
Doorleaf both sides with 1,0 mm galvanized steel sheet.
Frame like a z-profile around the door or with sill like a l-, u- or flatbar.
Frame for welding and bolting.
Doorleaf and frame primed.

Maximum size: 1200 x 2050 mm

Options:

- doorleaf with doorcloser
- doorleaf pvc-coated steel sheet
- doorleaf and frame stainless steel sheet
- frame with sealing
- doorleaf with recessed handles



Shipdoor A-60 "PK-AH 2000"

A-60 single-leaf hinged fire-door, type "PK-AH 2000",
EC-Certificate SBG-110.058, ABS, GL, RRS, TC, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.

Doorleaf both sides with 1,0 mm galvanised steel sheet.

Frame like a z-profile around the door or with sill like a I-, u- or flatbar.

Doorleaf and frame primed.

Maximum size: 1000 x 2000 mm

Options:

doorleaf with doorcloser

hoseport

doorleaf pvc-coated steel sheet

doorleaf and frame stainless steel sheet

frame with sealing

doorleaf with panic bar

doorleaf with recessed handles

doorleaf with electromagnet



Shipdoor A-60 "PK-AH 2000L"

A-60 single-leaf hinged fire-door, type "PK-AH 2000L",
EC-Certificate SBG-110.058, ABS, GL, RRS, TC, USCG.

Door complete with lock as per DIN 18250 and handle, lift lock and contact.
Doorleaf both sides with 1,0 mm galvanised steel sheet.
Frame like a special steel profile around the door or with sill like a I-, u- or flatbar.
Doorleaf and frame primed.

Maximum size: 1000 x 2000 mm

Options:

- doorleaf with doorcloser
- doorleaf and frame stainless steel sheet
- doorleaf pvc-coated steel sheet
- frame with sealing
- doorleaf with recessed handles



Shipdoor A-60 "LMD-SL-S"

A-60 single-leaf sliding fire-door, type "A60 LMD-SL-S",
GL-EC-Certificate 50665-03 Lux, ABS, RRS, TC, USCG.

Door complete with lock and handle, provided for cylinder, frame, railtrack, counterweight
and airbrake.

Doorleaf both sides with 1,5 mm galvanised steel sheet.

Frame around the door.

Frame for welding and bolting.

Doorleaf and frame primed.

Maximum size: 2310 x 2242mm

Weight: 50 kg/m² / doorleaf

Options:

hoseport

doorleaf pvc-coated steel sheet

doorleaf and frame stainless steel sheet

clamping frame

doorleaf with recessed handles

doorleaf with electromagnet

equipment with electric opening and closing system

equipment with pneumatic opening and closing system



Shipdoor A-60 "A60 Poki SR / LMD-HS-R"

A-60 single-leaf hinged fire-door, type "A60 Poki SR / LMD-HS-R",
Certificate USCG.

Door complete with three point latch, handle and plate, provided for cylinder.

Doorleaf both sides with 1,0 mm galvanised steel sheet.

Frame like a z-profile around the door or with sill like a I-, u- or flatbar.

Frame for welding and bolting.

Doorleaf and frame primed.

Maximum size: 1125 x 2100 mm

Weight: 54 kg/m² / doorleaf

Options:

doorleaf with doorcloser

hoseport

doorleaf pvc-coated steel sheet

doorleaf and frame stainless steel sheet

frame with sealing

doorleaf with panic bar

doorleaf with recessed handles

doorleaf with electromagnet



Shipdoor A-60 "LMD-HS-NR"

A-60 single-leaf hinged fire-door, not rebated type "LMD-HS-NR",
GL-EC-Certificate 46015-03 Lux, ABS, USCG.

Door complete with lock as per DIN 18250, handle and plate, provided for cylinder.
Doorleaf both sides with 1,0 mm galvanised steel sheet.
Frame like a z-profile around the door or with sill like a I-, u- or flatbar.
Frame for welding and bolting.
Doorleaf and frame primed.

Maximum size: 1150 x 2050 mm
Weight: 45 kg/m² / doorleaf

Options:

- doorleaf with doorcloser
- hoseport
- doorleaf pvc-coated steel sheet
- doorleaf and frame stainless steel sheet
- frame with sealing
- doorleaf with A/60 window
- doorleaf with electromagnet
- doorleaf with concealed doorcloser
- doorleaf with round corners
- doorleaf with lever dog
- doorleaf with recessed handles



Shipdoor A-60 "LMD-HD-NR"

A-60 double-leaf hinged fire-door, not rebated type "LMD-HD-NR",
GL-EC-Certificate 47033-03 Lux, ABS, BV, USCG.

Active doorleaf complete with lock as per DIN 18250, handle and plate,
provided for cylinder, non active leaf with automatic flush bolt.

Doorleaves both sides with 1,0 mm galvanised steel sheet.

Frame like a z-profile around the door or with sill like a I-, u- or flatbar.

Frame for welding and bolting. Doorleaves and frame primed.

Maximum size: 2250 x 2100 mm

Weight: 45 kg/m² / doorleaf

Options:

doorleaf with doorcloser

hoseport

doorleaf pvc-coated steel sheet

doorleaf and frame stainless steel sheet

frame with sealing

doorleaf with concealed doorcloser

doorleaf with lever dogs

doorleaf with recessed handles

doorleaf with electromagnet

doorleaf with doorselector



Shipdoor A-60 "A60-2 Poki DR / LMD-HD-R"

A-60 double-leaf hinged fire-door, type "A60-2 Poki DR / LMD-HD-R",
GL-EL-Certificate 50664-03 Lux, ABS, RRS, TC, USCG.

Active doorleaf complete with lock as per DIN 18250, handle and plate,
provided for cylinder, non active leaf with two lock system.

Doorleaves both sides with 1,0 mm galvanised steel sheet.

Frame like a z-profile around the door or with sill like a I-, u- or flatbar.

Frame for welding and bolting.

Doorleaves and frame primed.

Maximum size: 2250 x 2100 mm

Weight: 54 kg/m² / doorleaf

Options:

doorleaf with doorcloser

hoseport

doorleaf pvc-coated steel sheet

doorleaf and frame stainless steel sheet

frame with sealing

doorleaf with concealed doorcloser

doorleaf with panic bar

doorleaf with recessed handles

doorleaf with electromagnet

doorleaf with doorselector

doorleaf with 3-point-latch



Shipdoor A-60 "LMD-VSF 2"

A-60 double-leaf vertical sliding fire-door, type "LMD-VSF 2",
GL-EC-Certificate 42 493-02 Lux, USCG.

Door complete with lock and handle, frame, railtrack and rubber-bumper.
Doorleaves both sides with 1,5 mm galvanised steel sheet.
Doorleaves and frame primed.

Maximum size: 1000 x 1195 mm
Weight: 40 kg/m² / doorleaf

Options:

doorleaf and frame stainless steel sheet
doorleaf pvc coated steel sheet

